

Series KB-SW Type C Slideway Wiper

| Type | Order No | Protection | H | S | W | T | D | Length | Material |
|-----------|----------|--------------|----|------|---|----|----|--------|----------|
| KB-SW-C 1 | 1000197 | Spring steel | 25 | 15.5 | 3 | 12 | 29 | 800 mm | NBR |
| KB-SW-C 2 | 1000198 | Spring steel | 25 | 15.5 | 3 | 12 | 29 | 800 mm | FPM |
| KB-SW-C 3 | 1000199 | - | 25 | 15.5 | 3 | 12 | - | 800 mm | NBR |
| KB-SW-C 4 | 1000200 | - | 25 | 15.5 | 3 | 12 | - | 800 mm | FPM |
| KB-SW-C 5 | 1000113 | Spring steel | 30 | 20.5 | 3 | 12 | 34 | 800 mm | NBR |
| KB-SW-C 6 | 1000201 | Spring steel | 30 | 20.5 | 3 | 12 | 34 | 800 mm | FPM |
| KB-SW-C 7 | 1000087 | - | 30 | 20.5 | 3 | 12 | - | 800 mm | NBR |
| KB-SW-C 8 | 1000202 | - | 30 | 20.5 | 3 | 12 | - | 800 mm | FPM |

Moulded wipers Type C are the correct choice for applications in the cleaning of large steel plates, with surface inaccuracies. The flexible wiper lip compensates easily to this difficult application.

A lip preload of 4 mm can be attained, resulting in retaining a constant low surface contact friction area. As an added protection against hot chips, a high grade spring steel protection cover is vulcanised to the rubber lip system.

Elastomer compositions are NBR & FPM with a hardness of 75A. Standard colour is black. Additional hardness properties & colours are achievable by the uses of H-NBR.

Type C

Type KB-SW-C

Note: We normally stock these wipers in Nitrile Rubber (NBR)

